



Isometric view1: 1

Notes:

1. Materials: C7980 0F
2. Design Wavelength: 587.6nm
3. Focal Length:  $f = -100.0\text{mm} \pm 1\%$
4. Back Focal Length(REF):  $bf = -101.92\text{mm}$
5. Centration error:  $\leq 2$  arc min
6. Clear aperture:  $\geq 90\%$
7. G - Fine ground surface
8. Coating: AR/AR@700~1100nm(REFER TO COATING CURVES)
9. All dimensions are in mm

Parameters			<b>SHALOM EO</b> www.shalomeo.com		UVFS Plano-concave D=25.4 F=-100 WITH AR@700~1100nm COATING				
	S1	S2							
Shape	Convex	Plano							
Radius of curvature	-45.85	Infinity							
Surface quality	10/5 S/D	10/5 S/D	Proprietary	Name	Date	Part number	Rev	Scale	
Surface Irregularity	$\lambda/10@632.8\text{nm}$	$\lambda/10@632.8\text{nm}$	The drawing is property of Hangzhou Shalom EO, any reproduction in part or as a whole without permission is prohibited.	DRAWN	YSF	27/Apr/20	1104-033	A	2:1
Power(P-V)	$3\lambda/2@632.8\text{nm}$	$\lambda/2@632.8\text{nm}$		APPROVAL	JT	27/Apr/20			
Protective chamfers	0.2mm x 45°	0.2mm x 45°							